



Brisa® | Outdoor Collection



Acoustical properties • Breathable technology • EPA-registered anti-mildew • Solar endurance

For Contract, Hospitality and Residential Applications



393-3160 Durango

Original Outdoor



396-3972 Lasso*

Distressed Outdoor


Brisa® | Outdoor Collection




393-5750 Polar



396-3361 Mohave*




393-5267 Daisy



393-4435 Cricket




393-5852 Jasper




396-3733 Greige*



396-3980 Waylan*



393-4529 Glass



393-5875 Nimbus




396-3024 Chamois*



393-3823 Aztec




393-4528 Sea Green




396-3790 Shadow*




396-3134 Buckskin*




393-8214 Marigold



393-2542 Michigan Blue



393-5749 Black Onyx



396-3970 Chaps*



393-1331 Burnt Red

* Brisas® | Distressed Outdoor



Outdoor



Breathable

Brisa® | Outdoor Collection

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Polyester, 35% Rayon Backing

Weight:

Approx. 11.5 oz. Per Square Yard
Approx. 390 Grams Per Square Metre

Thickness:

Approx. 1.15 Millimetres

Width:

54 Inches / 137 Centimetres

Repeat:

8"V x 10.5"H / 203mm V x 267mm H
(Distressed Outdoor)

Performance

Abrasion:

ASTM D4157 / 200,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 180,000 Rubs (Martindale)*
*meets or exceeds

Hydrolysis:

14+ Weeks
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: ASTM D2261

Breaking Strength: ASTM D5034

Tensile Strength: BS EN ISO 1421

Air Permeability: ASTM D737

Anti-mildew: ASTM G21

Sound Absorption: ASTM C423

Colorfastness

UV:

ASTM G154, 1000 Hours

Light Fastness:

AATCC 16.3, 200 Hours, Grade 4
ISO 105 B02, Grade 6

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Chlorinated Water:

AATCC 162, Class 4-5

Perspiration:

AATCC 15, Class 5

Sea (Salt) Water:

AATCC 106, Class 4-5

Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- FAR Specifications
- IMO Part 8
- NFPA 701

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

