




# Uf<sup>2</sup> | Primera<sup>®</sup>



700-56842 Mist




700-34312 Ecru




700-44382 Seedling




700-34322 Rattan



700-25362 Spa



700-00042 Chalk



700-34882 Irish Lace




700-39542 Desert



700-34382 Toffee




700-25372 Chambray



700-56282 Slate




700-56842 Mist



700-34392 Carob



700-13092 Barn Red




700-25382 Blueprint




700-56392 Coal



700-34332 Fossil



700-34402 Java



700-13372 Merlot

General Specifications

|                                                                                          |                                                                                                                                                                                |                                                                                                                                                                                                                                                                    |
|------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Composition:</b><br>100% Polyurethane Surface<br>55% Rayon, 45% Polyester             | <b>Abrasion:</b><br>ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*<br>ASTM D3884 / 2,000 cycles (Taber)*<br>BS EN ISO 12947-2 / 200,000 Rubs (Martindale)*<br>*meets or exceeds | <b>Crocking:</b><br>AATCC 8, Class 4-5 Wet & Dry                                                                                                                                                                                                                   |
| <b>Weight:</b><br>Approx. 12.5 oz. Per Square Yard<br>Approx. 424 Grams Per Square Metre | <b>Hydrolysis:</b><br>7 Weeks<br>ISO 1419 Method C (Accelerated Ageing)                                                                                                        | <b>Light:</b><br>AATCC 16.3, 200 Hours, Grade 4                                                                                                                                                                                                                    |
| <b>Thickness:</b><br>Approx. 1.0 Millimetres                                             | <b>Adhesion of Coating:</b><br>ASTM D751                                                                                                                                       | <b>F/R Rating:</b><br>ASTM E84 (Adhered) - Class A<br>CA TB 117 - Pass<br>FMVSS 302 & 95/28 Annex IV - Pass<br>NFPA 260 - Class 1<br>UFAC - Class 1                                                                                                                |
| <b>Width:</b><br>54 Inches / 137 Centimetres                                             | <b>Tear Strength:</b><br>ASTM D2261                                                                                                                                            | <b>Please Note:</b> These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:<br><ul style="list-style-type: none"><li>• ASTM E84 (Unadhered)</li><li>• NFPA 701</li></ul> |
| <b>Repeat:</b><br>None                                                                   | <b>Breaking Strength:</b><br>ASTM D5034                                                                                                                                        |                                                                                                                                                                                                                                                                    |

Environmental Information

- Low VOCs (Volatile Organic Compounds)
- No Conflict Minerals
- No Heavy Metal Stabilizers
- No Flame Retardants (Halogenated, Brominated: ex. PBDEs)
- No PBDEs (Polybrominated Diphenyl Ethers)
- No Plasticizer Phthalates
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)

For more information on our fabrics, cleaning and care instructions, please visit our website.

