




# Ultraleather® | Fusion Shimmer



A subtle sparkle effect enhances the smooth, understated look of **Ultraleather® | Fusion Shimmer**. Available in an elegant, focused color palette, Shimmer creates a luxurious aesthetic in any setting.

#### Distinctive Characteristics:

- Superior durability – industry-leading 14+ weeks hydrolysis results
- Blended backcloth for expanded upholstery capabilities
- 150,000 double rubs (Wyzenbeek), 150,000 rubs (Martindale)
- Bleach cleanable (1:5 bleach/water solution)
- SCS Indoor Advantage Gold Certification
- Meets Health Care Without Harm's Healthy Interiors Criteria V2.3

Providing hard-working upholstery solutions—the Ultraleather® family redefines performance fabrics with classic aesthetics and authentic softness.

# Ultraleather® | Fusion Shimmer

---

## General Specifications

### Composition:

100% Polycarbonate Polyurethane Surface  
65% Polyester, 35% Rayon Backing

### Weight:

Approx. 10.6 oz. Per Square Yard  
Approx. 360 Grams Per Square Metre

### Thickness:

Approx. 1.05 Millimetres

### Width:

54 Inches / 137 Centimetres

### Repeat:

None

## Performance

### Abrasion:

ASTM D4157 / 150,000 Double Rubs (Wyzenbeek)\*  
BS EN ISO 12947-2 / 150,000 Rubs (Martindale)\*

\*meets or exceeds

### Hydrolysis:

14+ Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability)  
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: ASTM D2261

Breaking Strength: ASTM D5034

Tensile Strength: BS EN ISO 1421

## Colorfastness

### Light Fastness:

AATCC 16.3, 200 Hours, Grade 4  
ISO 105 B02, Grade 6

### Crocking:

AATCC 8, Grade 4-5 Wet & Dry

## Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- FAR Specifications
- IMO Part 8
- NFPA 701

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website..

