



Ultraleather® | Pebble Outdoor



Ultraleather® | Pebble Outdoor is extremely resilient and meticulously engineered, providing protection that lasts. EPA-registered anti-mildew defense and enhanced fade resistance to sunlight and other harsh elements will preserve your upholstery's good looks for years to come. Subtle tone-on-tone warm neutrals highlight the organic granular patterning. **Pebble Outdoor** is a timeless addition to any design vision, in any application, inside or out.

Distinctive Characteristics:

- Superior durability – industry-leading 14+ weeks hydrolysis results
- Blended backcloth for expanded upholstery capabilities
- 400,000 double rubs (Wyzenbeek), 200,000 rubs (Martindale)
- EPA-registered antimicrobial protection does not contain triclosan and triclocarban
- Bleach cleanable (1:5 bleach/water solution)
- SCS Indoor Advantage Gold Certification

Providing hard-working upholstery solutions – the Ultraleather® family redefines performance fabrics with classic aesthetics and authentic softness.



Outdoor



Antimicrobial

Ultraleather® | Pebble Outdoor

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Polyester, 35% Rayon Backing

Weight:

Approx. 10.9 oz. Per Square Yard
Approx. 370 Grams Per Square Metre

Thickness:

Approx. 1.15 Millimetres

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*
BS EN ISO 12947-2 / 200,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

14+ Weeks
ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: ASTM D2261

Breaking Strength: ASTM D5034

Tensile Strength: BS EN ISO 1421

Antibacterial: AATCC 147

Antimicrobial: ASTM E2180

Anti-mildew: ASTM G21

Colorfastness

UV:

ASTM G154, 1000 Hours

Light Fastness:

AATCC 16.3, 200 Hours, Grade 4
ISO 105 B02, Grade 6

Crocking:

AATCC 8, Grade 4-5 Wet & Dry

Chlorinated Water:

AATCC 162, Class 4-5

Perspiration:

AATCC 15, Class 5

Sea (Salt) Water:

AATCC 106, Class 4-5

Flammability Requirements

- ASTM E84 (Adhered) - Class A
- CA TB 117 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

- ASTM E84 (Unadhered)
- BS 5852 Source 0, 1 & 5 (Cig, Match & Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- FAR Specifications
- IMO Part 8
- NFPA 701

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



INDOOR ADVANTAGE GOLD FURNITURE

ultrafabricsinc.com

Ultrafabrics® and logo, and Ultraleather® are trademarks of Ultrafabrics Inc. Made in Japan.

9/19

